

# BLUE EXPLOSION



BLUE EXPLOSION POL RECT.  
60X120 / 24"X48" P34/M

BLUE EXPLOSION POL RECT.  
120X120 / 24"X48" P52/M

**Blue Explosion is a natural stone with a magnetic charisma, which offers us the opportunity to give free rein to creativity and imagination. This collection evokes new lifestyle trends thanks to its shades which are able to give harmonious forms to spaces.**

**Blue Explosion es una piedra natural con un carisma magnético, que nos brinda la oportunidad de dar rienda suelta a la creatividad y la imaginación. Esta colección evoca nuevas tendencias de estilo de vida gracias a sus matices capaces de dar forma armoniosa a los ambientes.**



MALLA WOAD 30X30 / WOAD MATT RECT 60X120 / BLUE EXPLOSION POL. RECT. 60X120 / TRIANA DESIERTO RECT. 20X120

## BLUE EXPLOSION POL RECT 60X120

REFERENCE	SIZE (cm)	THICKNESS (mm)	GROUP
<b>A037934</b>	60x120	10,50	



### DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requirements
---	--------------	----------------------------------

### PHYSICAL PROPERTIES

Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	=> 40 N/mm <sup>2</sup>
Abrasion resistance (glazed Ceramic)	EN ISO 10545-07	II
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

### CHEMICAL PROPERTIES

Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

## ROD. BLUE EXPLOSION POL. 7,5X60

REFERENCE	SIZE (cm)	THICKNESS (mm)	GROUP
<b>A038355</b>	7,5x60	0,00	



### DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requirements
---	--------------	----------------------------------

### PHYSICAL PROPERTIES

Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	=> 40 N/mm <sup>2</sup>
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

### CHEMICAL PROPERTIES

Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5